



Put Modbus devices on a BACnet IP network and Vice Versa!

SNMP and WiFi Sensor Support, too!

Control Solutions' Babel Buster BB2-7010

is a BACnet IP client/server device that functions as a Modbus RTU master/slave and/or Modbus TCP client/server. A large number of BACnet objects gives you flexibility in mapping Modbus registers to any combination of BACnet objects. Packed Modbus registers may be parsed to multiple BACnet objects when reading. Multiple BACnet objects may be packed into a single Modbus register when writing. All standard Modbus register types are supported.

Value objects will poll their assigned Modbus register at the interval you specify. The content of the Modbus register will be given as the Present Value of the BACnet object when read. The Modbus register is written each time the BACnet Value object is written. The Value object corresponds well the the Modbus Holding register.

Input objects will poll their assigned Modbus register at the interval you specify, and provide the Modbus data as the Present Value when read. Commandable Output objects are used to write Modbus registers, and will update the Modbus device each time BACnet is updated.

The BB2-7010-01 can be Modbus RTU master or slave, is concurrent Modbus TCP client and server, and is concurrent BACnet IP client and server. The BB2-7010-02 adds SNMP client and server. Read/write data from any of these protocols to another via BACnet objects retained in the local database of the BB2-7010. The BB2-7010-06 includes support for WiFi sensors.

Babel Buster BB2-7010 Object Summary

- *Analog Input, Analog Output, Analog Value*
- *Binary Input, Binary Output, Binary Value*
- *Multi-State Input, Output, Value*

- *Pool of 1000 objects for BB2-7010-01*
- *Pool of 500 objects for BB2-7010-02, -06*

- *Objects from pool can be assigned to any of above types*
- *Maximum of 250 Binary objects, includes state text*
- *Maximum of 1024 states for multi-state, includes state text (actual value supported varies by resource usage per object)*

- *Maximum of 200 dual-channel WiFi sensors supported (applies to model BB2-7010-06 only)*

Visit our web site for

- *Full details*
- *User Guides & Software Downloads*
- *Pricing & On-line Ordering*

www.csimn.com
651-426-4410 • 800-872-8613



Built-In Web Server
for Configuration and Diagnostics



Read/Write any standard Modbus Register
as a BACnet Property Value,
or vice versa!

FEATURES

- Read/Write any standard Modbus register via BACnet objects
 - Pool of 1000 objects
 - Analog, Binary, Multi-State object types
 - Input, Output, Value objects
- BACnet slave is Modbus RTU master or vice versa
- BB2-7010 is also Modbus TCP client/server
- Bidirectional communication between BACnet and Modbus
- Supports Modbus “coils”, input registers, holding registers
- Single or double Modbus registers, signed, unsigned, IEEE 754
- Modbus register mapping configured via web interface
- Modbus registers may be scaled (x10, x100, x0.1, x0.01, etc.)
- Modbus (master) polling interval configurable per point
- SNMP client and server capability
- WiFi sensor support for specific sensors
- Commandable BACnet objects implement priority array
- Hardened EIA-485 transceiver for Modbus RTU
- 10/100BaseT Ethernet for BACnet IP and Modbus TCP
- Powered by 12-24V DC/AC 50/60 Hz
- Power Consumption: 0.1A @ 24VDC
- DIN rail mounting, 100mm H x 70mm W x 60mm D
- Pluggable screw terminal block for power & RTU network
- Operating temperature -40°C to +85°C
- Humidity 5% to 90% non-condensing
- FCC Class A, CE Mark
- Listed to UL 916 and (Canadian) C22.2 No. 205-M1983

BACnet Protocol Implementation Conformance Statement (Abbreviated)

Date: 30 December 2013

Vendor Name: Control Solutions, Inc.

Product Name: Babel Buster BB2-7010-01/02/06

Product Model Number: BB2-7010

Applications Software Version: 2.35

Firmware Revision: 2.35

BACnet Protocol Revision: 7

Product Description: Network gateway allowing Modbus RTU and TCP devices, SNMP devices, and WiFi sensors to be accessed via BACnet IP.

BACnet Standardized Device Profile (Annex L):

▶ *BACnet Smart Sensor (B-SS)*

▶ *BACnet Smart Actuator (B-SA)*

List all BACnet Interoperability Building Blocks Supported (Annex K):

DS-RP-B, DS-RPM-B, DS-WP-B, DS-COV-B, DS-COVP-B,

DM-DDB-B, DM-DOB-B, DM-RD-B

Segmentation Capability: Request & response, window size 8

Standard Object Types Supported:

Object types: AI, AO, AV, BI, BO, BV, MSI, MSO, MSV, DEV (all static)

See additional documentation for optional & proprietary properties.

Data Link Layer Options:

▶ *BACnet IP (Annex J)*

Device Address Binding:

Is static device binding supported? No

Networking Options: BBMD, supports registration by foreign devices

Character Sets Supported: ANSI X3.4

If this product is a communication gateway, describe the types of non-BACnet equipment/networks(s) that the gateway supports:

Modbus RTU and/or Modbus TCP slaves/servers (BACnet slave device functions as Modbus RTU or TCP master), SNMP (-02), WiFi sensor data via UDP (-06)

Visit our web site for

- *Full details*
- *User Guides & Software Downloads*
- *Pricing*
- *On-Line Ordering*

www.csimmn.com



CONTROL SOLUTIONS MINNESOTA

PO BOX 10789

ST. PAUL, MN 55110-0789

VOICE (651) 426-4410 • FAX (651) 426-4418

TOLL FREE 1-800-872-8613

© 2019 Control Solutions, Inc. Babel Buster® is a registered trademark of Control Solutions, Inc. BACnet® is a registered trademark of American Society of Heating, Refrigerating and Air-Conditioning Engineers, Inc.